

Size	Load Index Single/Dual	Ply Rating	Sidewall	Standard Rim	Approved Rim Width	Overall Diameter	Section Width	Tread Depth in 32nds	Max Load	Max Pressure
265/70R16	112 Q	SL	BLK	8.0J	7.0-9.0	30.5	10.8	19	2470	44
31X10.50R15LT	109 Q	6	BLK	8.5J	7.0-9.0	31.1	10.7	19	2270	50
33X12.50R15LT	108 P	6	BLK	10.0J	9.0-11.0	33.0	12.8	21	2205	50
LT265/70R16	117/114 Q	8	BLK	8.0J	7.0-8.5	30.6	10.7	19	2835/2600	65
LT265/75R16	123 Q	10	BLK	7.5J	7.0-8.0	31.8	10.3	19	3415	80
LT285/75R16	126 Q	10	BLK	8.0J	7.5-9.0	32.9	11.2	21	3750	80
37X12.50R16.5LT	133 N	10	BLK	10.0J	8.25-9.75	37.0	12.8	21	4540	65
265/65R17	116 Q	XL	BLK	8.0J	7.5-9.5	30.5	10.8	19	2778	50
LT265/65R17	120/117 Q	10	BLK	8.0J	7.5-9.5	30.5	10.8	19	3085/2835	80
LT265/70R17	121 Q	10	BLK	8.0J	7.0-8.5	32.0	10.8	19	3195	80
LT285/70R17	126 Q	10	BLK	8.5J	7.5-9.0	32.8	11.5	21	3750	80
33X12.50R17LT	120 Q	10	BLK	10.0J	8.5-11.0	33.0	12.8	21	3042	80
35X12.50R17LT	125 Q	10	BLK	10.0J	8.5-11.0	34.8	13.2	21	3640	80
37X12.50R17LT	124 Q	8	BLK	10.0J	8.5-11.0	37.0	12.8	21	3525	50
37X12.50R17.5LT	133 N	10	BLK	10.0J	8.5-11.0	37.0	12.8	21	4540	65
37X13.50R17LT	131 Q	10	BLK	11.0J	8.5-11.0	37.0	16.4	21	4300	65
LT285/65R18	125 Q	10	BLK	8.5J	8.0-10.0	32.6	11.5	19	3640	80
33X12.50R18LT	118 Q	10	BLK	10.0J	8.5-11.0	33.0	12.7	21	2910	80
35X12.50R18LT	123 Q	10	BLK	10.0J	8.5-11.0	35.0	13.2	21	3415	80
38X15.50R18LT	128 Q	8	BLK	12.0J	11.0-13.0	37.7	15.9	21	3970	50
255/55R19	111 Q	XL	BLK	8.5J	7.0-9.0	33.0	10.4	19	2049	50
265/50R20	111 Q	XL	BLK	8.5J	7.5-9.5	30.5	10.9	19	2049	50
33X12.50R20LT	114 Q	10	BLK	10.0J	8.5-11.0	33.0	13.0	21	2600	65
35X12.50R20LT	121 Q	10	BLK	10.0J	8.5-11.0	35.0	13.0	21	3195	80
37X12.50R20LT	126 Q	10	BLK	10.0J	8.5-11.0	37.0	12.8	21	3750	65
37X13.50R20LT	127 Q	10	BLK	11.0J	8.5-11.0	37.0	14.0	21	3860	65
38X15.50R20LT	125 Q	8	BLK	12.0J	11.0-13.0	37.7	15.9	21	3640	50
40X15.50R20LT	130 Q	8	BLK	12.0J	11.0-13.0	39.7	15.9	21	4190	50
33X12.50R22LT	109 Q	10	BLK	10.0J	9.0-11.0	33.0	13.4	21	2270	65
35X12.50R22LT	117 Q	10	BLK	10.0J	9.0-11.0	35.0	12.8	21	2835	65
37X13.50R22LT	123 Q	10	BLK	11.0J	8.5-11.0	37.0	14.0	21	3420	65
38X15.50R22LT	124 Q	8	BLK	12.0J	11.0-13.0	37.7	15.9	21	3525	50
40X15.50R22LT	127 Q	8	BLK	12.0J	11.0-13.0	39.7	15.9	21	3860	50

37X13.50R24LT	120 Q	10	BLK	11.0J	8.5-11.0	37.0	14.0	21	3085	65
40X15.50R24LT	128 P	10	BLK	12.0J	11.0-13.0	39.7	15.9	21	3970	65
37X13.50R26LT	117 Q	10	BLK	11.0J	8.5-11.0	37.0	14.0	21	2835	65