

Size	Service Description	Ply Rating	Sidewall	Standard Rim	Approved Rim Width	Overall Diameter	Section Width	Tread Depth in 32nds	Max Load Single/Dual	Max Pressure
235/75R15	109 S	XL	BLK	6.5J	6.0-8.0	28.9	9.3	13	2270	50
LT235/75R15	104/101 S	6	BLK	6.5J	6.0-7.0	28.9	9.3	16	1985/1820	50
31X10.50R15LT	109 S	6	BLK	8.5J	7.0-9.0	30.5	10.6	16	2270	50
235/70R16	109 T	XL	BLK	7.0J	6.0-8.0	29.0	9.4	13	2270	50
245/70R16	111 T	XL	BLK	7.0J	6.5-8.0	29.5	9.8	13	2403	50
255/70R16	112 S	XL	BLK	7.5J	6.5-8.5	30.1	10.2	13	2469	50
LT305/70R16	124/121 R	10	BLK	9.0J	8.0-9.5	32.8	12.2	17	3525/3195	65
LT225/75R16	115/112 Q	10	BLK	7.0J	6.0-7.0	29.3	8.8	15	2680/2470	80
P245/75R16	109 S		BLK	7.0J	6.5-8.0	30.5	9.8	13	2270	44
LT245/75R16	108/104 S	6	BLK	7.0J	6.5-7.5	30.5	9.8	16	2205/2006	50
LT245/75R16	120/116 S	10	BLK	7.0J	6.5-7.5	30.5	9.8	16	3042/2778	80
LT265/75R16	112/109 T	6	BLK	7.5J	7.0-8.0	31.7	10.5	16	2470/2270	50
LT265/75R16	123/120 R	10	BLK	7.5J	7.0-8.0	31.7	10.5	16	3415/3085	80
LT285/75R16	126/123 R	10	BLK	8.0J	7.5-9.0	32.8	11.3	17	3750/3415	80
LT215/85R16	115/112 Q	10	BLK	6.0J	5.5-7.0	30.4	8.5	15	2680/2470	80
LT235/85R16	120/116 R	10	BLK	6.5J	6.0-7.0	31.7	9.3	16	3042/2778	80
35X12.50R17LT	121 R	10	BLK	10.0J	8.5-11.0	34.5	12.5	17	3195	65
245/65R17	111 T	XL	BLK	8.5J	7.0-8.5	29.5	9.8	13	2403	50
265/65R17	116 S	XL	BLK	8.0J	7.5-9.5	30.5	10.8	13	2778	44
P245/70R17	108 S		BLK	7.0J	6.5-8.0	30.6	9.8	13	2205	44
LT245/70R17	119/116 R	10	BLK	7.0J	6.5-8.0	30.6	9.8	16	3000/2755	80
LT265/70R17	121/118 S	10	BLK	8.0J	7.0-8.5	31.7	10.7	16	3195/2910	80
LT285/70R17	121/118 S	10	BLK	8.5J	7.5-9.0	32.8	11.5	16	3195/2910	80
LT245/75R17	121/118 S	10	BLK	7.0J	6.5-7.5	31.5	9.8	16	3195/2910	80
35X12.50R18LT	123 R	10	BLK	10.0J	8.5-11.0	34.5	12.5	17	3415	65
LT275/65R18	123/120 T	10	BLK	8.0J	7.5-9.5	32.1	11.0	16	3415/3085	80
LT285/65R18	125/122 S	10	BLK	8.5J	8.0-10.0	32.6	11.5	17	3640/3305	80
35X12.50R20LT	121 R	10	BLK	10.0J	8.5-11.0	34.5	12.5	17	3195	65
LT285/55R20	122/119 S	10	BLK	9.0J	8.0-10.0	32.4	11.7	16	3305/3000	80
LT305/55R20	121/118 S	10	BLK	9.5J	8.5-11.0	33.2	12.4	16	3195/2910	80
LT275/65R20	126/123 T	10	BLK	8.0J	7.5-9.5	34.1	11.0	16	3750/3415	80
LT325/50R22	122 R	10	BLK	10.0J	9.0-12.0	34.8	13.2	17	3305	65